PATENT ABSTRACTS OF JAPAN

(11)Publication number:

2001-266704

(43) Date of publication of application: 28.09.2001

(51)Int.CI.

H01H 19/14 B60R 21/045

(21)Application number: 2000-080038

(71)Applicant: MATSUSHITA ELECTRIC IND CO LTD

(22)Date of filing: 22.03.2000 (72)Inventor


(72)Inventor: HOSHINO SATORU

(54) KNOB APPARATUS

(57)Abstract:

PROBLEM TO BE SOLVED: To obtain an operating knob, capable of absorbing impact using a simple and inexpensive structure.

SOLUTION: A knob 11 comprises an inside knob part 13, having a piercing shaft hole 17 which is fitted to a shaft 28 of a variable resistor 27, and an outside knob part 12 fitted to an outer part of the inside knob part 13. An impact—absorbing projection 11, which is breakable from a collision with the tip of the shaft 28 of the variable resistor, is provided inside the through—hole 17. Thereby, the operating knob capable of absorbing impact can be achieved by an inexpensive and simple structure formed merely by assembling the resin—molded outside knob part 12 and the inside knob part 13.



LEGAL STATUS

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's decision of rejection]

[Date of extinction of right]